encryption, so the client should ensure that the received ID token uses these algorithms. The client should then verify the standard JWT claims in the ID token, such as the expiry, issuer, and audience values as described in chapter 6. OIDC defines several additional claims that should also be verified, described in table 7.4.

Table 7.4 ID token standard claims

Claim	Purpose	Notes
`azp`	Authorized Party	An ID token can be shared with more than one party and so have multiple values in the audience claim. The azp claim lists the client the ID token was initially issued to. A client directly interacting with an OIDC provider should verify that it's the authorized party if more than one party is in the audience.
`auth_time`	User authentication time	The time at which the user was authenticated as seconds from the UNIX epoch.
`nonce`	Anti-replay nonce	A unique random value that the client sends in the authentication request. The client should verify that the same value is included in the ID token to prevent replay attacks—see section 7.6.2 for details.
`acr`	Authentication context Class Reference	Indicates the overall strength of the user authentication performed. This is a string and specific values are defined by the OP or by other standards.
`amr`	Authentication Methods References	An array of strings indicating the specific methods used. For example, it might contain `["password", "otp"]` to indicate that the user supplied a password and a one-time password.

When requesting authentication, the client can use extra parameters to the authorization endpoint to indicate how the user should be authenticated. For example, the `max_time` parameter can be used to indicate how recently the user must have authenticated to be allowed to reuse an existing login session at the OP, and the `acr_values` parameter can be used to indicate acceptable authentication levels of assurance. The `prompt=login` parameter can be used to force re-authentication even if the user has an existing session