```
└── AppTest.java #C
```

#A The Maven project file.
#B The sample Java class generated by Maven.
#C A sample unit test file.

You first need to replace the generated Maven project file with one that lists the dependencies that you'll use. Locate the pom.xml file and open it in your favorite editor or IDE. Select the entire contents of the file and delete it, then paste the contents of the following listing into the editor and save the new file. This ensures that Maven is configured for Java 11, sets up the main class to point to the `Main` class (to be written shortly), and configures all the dependencies you need.

Listing 2.1 pom.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">
<modelVersion>4.0.0</modelVersion>
<groupId>com.manning.api-security-in-action</groupId>
<artifactId>natter-api</artifactId>
<version>1.0.0-SNAPSHOT</version>
<properties>
<maven.compiler.source>11</maven.compiler.source> #A
<maven.compiler.target>11</maven.compiler.target> #A
<exec.mainClass>
com.manning.apisecurityinaction.Main #B
</exec.mainClass>
</properties>
```