```
msg_time TIMESTAMP NOT NULL DEFAULT CURRENT_TIMESTAMP,
msg_text VARCHAR(1024) NOT NULL
);
CREATE SEQUENCE msg_id_seq;
CREATE INDEX msg_timestamp_idx ON messages(msg_time); #D
CREATE UNIQUE INDEX space_name_idx ON spaces(name);
```

#A The spaces table describes who owns which social spaces.
#B We use sequences to ensure uniqueness of primary keys.
#C The messages table contains the actual messages.
#D We index messages by timestamp to allow catching up on recent messages.

Fire up your editor again and create the file Main.java under natter-api/src/main/java/com/manning/apisecurityinaction (where Maven generated the App.java for you earlier). The following listing shows the contents of this file. In the main method, you first create a new `JdbcConnectionPool` object. This is a H2 class that implements the standard JDBC `DataSource` interface, while providing simple pooling of connections internally. You can then wrap this in a Dalesbred `Database` object using the `Database.forDataSource()` method. Once you've created the connection pool, you can then load the database schema from the schema.sql file that you created earlier. When you build the project, Maven will copy any files in the src/main/resources file into the .jar file it creates. You can therefore use the `Class.getResource()` method to find the file from the Java classpath, as shown in listing 2.3.

**Listing 2.3 Setting up the database connection pool**

```
package com.manning.apisecurityinaction;
```