Listing 10.15 Checking for local IP addresses

```
private static boolean isBlockedAddress(String uri)
        throws UnknownHostException {
    var host = URI.create(uri).getHost();    #A
    for (var ipAddr : InetAddress.getAllByName(host)) {    #B
        if (ipAddr.isLoopbackAddress() ||    #C
                ipAddr.isLinkLocalAddress() ||    #C
                ipAddr.isSiteLocalAddress() ||    #C
                ipAddr.isMulticastAddress() ||    #C
                ipAddr.isAnyLocalAddress() ||     #C
                isUniqueLocalAddress(ipAddr)) {    #C
            return true;    #C
        }
    }
    return false;    #D
}

private static boolean isUniqueLocalAddress(InetAddress
ipAddr) {
    return ipAddr instanceof Inet6Address &&    #E
            (ipAddr.getAddress()[0] & 0xFF) == 0xFD &&    #E
            (ipAddr.getAddress()[1] & 0xFF) == 0X00;    #E
}
```

#A Extract the hostname from the URI
#B Check all IP addresses for this hostname
#C Check if the IP address is any local or private use type
#D Otherwise, return false
#E To check for IPv6 unique local addresses, check the first two bytes of the raw address

You can now update the link-preview operation to reject requests using a URL that resolves to a local address by changing the implementation of the GET request handler to