If you then request a message that contains a link to trigger a call to the link-preview service (using the steps at the end of section 10.2.6), you'll see the network requests in the tap output. This shows the initial request from curl without TLS (tls=not_provided_by_remote), followed by the request to the link-preview service with TLS enabled (tls=true). Finally, the response is returned to curl without TLS:

```
req id=2:0 proxy=in  src=172.17.0.1:57757
dst=172.17.0.4:4567    #A
[CA]tls=not_provided_by_remote :method=GET :authority=    #A
[CA]natter-api-service:4567 :path=/spaces/1/messages/1    #A
req id=2:1 proxy=out src=172.17.0.4:53996
dst=172.17.0.16:4567    #B
[CA]tls=true :method=GET :authority=natter-link-preview-    #B
[CA]service:4567 :path=/preview    #B
rsp id=2:1 proxy=out src=172.17.0.4:53996
dst=172.17.0.16:4567    #B
[CA]tls=true :status=200 latency=479094µs    #B
end id=2:1 proxy=out src=172.17.0.4:53996
dst=172.17.0.16:4567    #B
[CA]tls=true duration=665µs response-length=330B    #B
rsp id=2:0 proxy=in  src=172.17.0.1:57757
dst=172.17.0.4:4567    #B
[CA]tls=not_provided_by_remote :status=200 latency=518314µs
#C
end id=2:0 proxy=in  src=172.17.0.1:57757     #C
[CA]dst=172.17.0.4:4567 tls=not_provided_by_remote
duration=169µs   #C
[CA]response-length=428B    #C
```

#A The initial response from curl is not using TLS
#B The internal call to the link-preview service is upgraded to TLS
#C The response back to curl is also sent without TLS