		one. The “optional_no_ca” option prompts the client for a certificate but doesn’t verify it.
`nginx.ingress.kubernetes.io/auth-tls-secret`	The name of a Kubernetes secret in the form `"namespace/secret-name"`	The secret contains the set of trusted CAs to verify the client certificate against.
`nginx.ingress.kubernetes.io/auth-tls-verify-depth`	A positive integer	The maximum number of intermediate CA certificates allowed in the client’s certificate chain.
`nginx.ingress.kubernetes.io/auth-tls-pass-certificate-to-upstream`	`"true"` or `"false"`	If enabled, the client’s certificate will be made available in the `ssl-client-cert` HTTP header to servers behind the ingress.
`nginx.ingress.kubernetes.io/auth-tls-error-page`	A URL	If certificate authentication fails, the client will be redirected to this error page.

To create the secret with the trusted CA certificates to verify any client certificates, you create a generic secret passing in a PEM-encoded certificate file. You can include multiple root CA certificates in the file by simply listing them one after the other. For the examples in this chapter, you can use client certificates generated by the `mkcert` utility that you’ve used since chapter 2. The root CA certificate for `mkcert` is installed into its CAROOT directory, which you can determine by running

```
mkcert -CAROOT
```

which will produce output like the following:

```
/Users/neil/Library/Application Support/mkcert
```