> **TIP** Linkerd is planning to add support for forwarding the client certificate in a header in a future release.

Unlike Nginx, which uses separate headers for different fields extracted from the client certificate, Istio combines the fields into a single header like the following example:[4]

```
x-forwarded-client-cert: By=http://frontend.lyft.com;Hash=
[CA]468ed33be74eee6556d90c0149c1309e9ba61d6425303443c0748a
[CA]02dd8de688;Subject="CN=Test Client,OU=Lyft,L=San
[CA] Francisco,ST=CA,C=US"
```

The fields for a single certificate are separated by semicolons, as in the example. The valid fields are given in table 11.3.

Table 11.3 Istio X-Forwarded-Client-Cert fields

Field	Description
`By`	The URI of the proxy that is forwarding the client details.
`Hash`	A hex-encoded SHA-256 hash of the full client certificate
`Cert`	The client certificate in URL-encoded PEM format
`Chain`	The full client certificate chain, in URL-encoded PEM format
`Subject`	The Subject DN field as a double-quoted string
`URI`	Any URI-type SAN entries from the client certificate. This field may be repeated if there are multiple entries.
`DNS`	Any DNS-type SAN entries. This field can be repeated if there's more than one matching SAN entry.

The behavior of Istio when setting this header is not configurable and depends on the version of Istio being used. The latest version, 1.4.3, sets the `By`, `Hash`, `Subject`, `Uri`, and `Dns`