```
    var database = Database.forDataSource(pool);    #A

    database.update("CREATE TABLE devices(" +    #B
            "device_id VARCHAR(30) PRIMARY KEY," +    #B
            "manufacturer VARCHAR(100) NOT NULL," +    #B
            "model VARCHAR(100) NOT NULL," +    #B
            "encrypted_psk VARBINARY(1024) NOT NULL)");    #B

    var out = new ByteArrayOutputStream();    #C
    encryptedPsk.writeTo(out);    #C
    database.update("INSERT INTO devices(" +    #D
            "device_id, manufacturer, model, encrypted_psk) "
+    #D
            "VALUES(?, ?, ?, ?)", "test", "example",
"ex001",    #D
            out.toByteArray());    #D

    return database;
}
```

#A Create and load the in-memory device database
#B Create a table to hold device details and encrypted PSKs
#C Serialize the example encrypted PSK to a byte array
#D Insert an example device into the database

You'll also need a way to find a device by its device ID or other attributes. Dalesbred makes this quite simple, as shown in listing 13.3. The `findOptional` method can be used to search for a device; it will return an empty result if there is no matching device. You should select the fields of the device table in exactly the order they appear in the `Device` class constructor in listing 13.1. As described in chapter 2, use a bind parameter in the query to supply the device ID, to avoid SQL injection attacks.