A.1 summarizes the relevant values from the configuration. See chapter 7 for a description of these endpoints.

Table A.1 ForgeRock AM OAuth2 endpoints

Endpoint name	URI
Token endpoint	http://as.example.com:8080/oauth2/access_token
Introspection endpoint	http://as.example.com:8080/oauth2/introspect
Authorization endpoint	http://as.example.com:8080/oauth2/authorize
UserInfo endpoint	http://as.example.com:8080/oauth2/userinfo
JWK Set URI	http://as.example.com:8080/oauth2/connect/jwk_uri
Dynamic client registration endpoint	http://as.example.com:8080/oauth2/register
Revocation endpoint	http://as.example.com:8080/oauth2/token/revoke

To register an OAuth2 client, click on Applications in the left-hand sidebar, then OAuth2, and then Clients. Click the New Client button and you'll see the form for basic client details shown in figure A.4. Give the client an ID and a client secret. You can choose a weak client secret for development purposes; I use "password". Finally, you can configure some scopes that the client is permitted to ask for.

> **TIP** By default, AM only supports the basic OpenID Connect scopes: openid, profile, email, address, and phone. You can add new scopes by clicking on Services in the left-hand sidebar, then OAuth2 Provider. Then click on the Advanced tab and add the scopes to the Supported Scopes field and click Save Changes.