The LB node depends on the DB node and the two VM nodes. The CDN node depends on the LB and the bucket node. Finally, the DNS node depends on the CDN node.

The JIML tool turns the dependency graph into a linear flow of commands using pseudo language, as shown in the next listing. The pseudo language represents the steps needed to create all the resources in the correct order. The nodes are easy to create because they have no dependencies, so they're created first.

Listing 4.9 Linear flow of commands in pseudo language

```
$DB = database create {"password": "***",                    ①
➥ "engine": "MySQL"}
$VM1 = virtualmachine create {"cpu": 2, "ram": 4,            ②
➥ "os": "ubuntu"}
$VM2 = virtualmachine create {"cpu": 2, "ram": 4,
➥ "os": "ubuntu"}
$BUCKET = bucket create {}                                   ③

await [$DB, $VM1, $VM2]                                      ④
$LB = loadbalancer create {"virtualmachines":                ⑤
➥ [$VM1, $VM2]}

await [$LB, $BUCKET]
$CDN = cdn create {...}                                      ⑥

await $CDN
$DNS = dns create {...}                                      ⑦

await $DNS
```

① Creates the database

② Creates the virtual machine

③ Creates the bucket

④ Waits for the dependencies

⑤ Creates the load balancer

⑥ Creates the CDN

⑦ Creates the DNS entry