https://aws.amazon.com/quickstart/. Furthermore, we have open sourced the templates we are using in our day-to-day work on GitHub: https://github.com/widdix/aws-cf-templates.

Suppose you've been asked to provide a VM for a developer team. After a few months, the team realizes the VM needs more CPU power, because the usage pattern has changed. You can handle that request with the CLI and the SDK, but before the instance type can be changed, you must stop the EC2 instance. The process follows:

1. Stop the instance.
2. Wait for the instance to stop.
3. Change the instance type.
4. Start the instance.
5. Wait for the instance to start.

A declarative approach like that used by CloudFormation is simpler: just change the `InstanceType` property and update the template. `InstanceType` can be passed to the template via a parameter, as shown in the next listing. That's it! You can begin creating the template.

Listing 4.16 A template to create an EC2 instance with CloudFormation

```
---
AWSTemplateFormatVersion: '2010-09-09'
Description: 'AWS in Action: chapter 4'
Parameters:
  VPC:                                                    ①
    Type: 'AWS::EC2::VPC::Id'
  Subnet:                                                 ①
    Type: 'AWS::EC2::Subnet::Id'
  InstanceType:                                           ②
    Description: 'Select one of the possible instance types'
    Type: String
    Default: 't2.micro'
    AllowedValues: ['t2.micro', 't2.small', 't2.medium']
Resources:
  SecurityGroup:                                          ①
```