```
    Type: 'AWS::EC2::SecurityGroup'
    Properties:
      # [...]
  VM:                                                    ③
    Type: 'AWS::EC2::Instance'
    Properties:
      ImageId: 'ami-061ac2e015473fbe2'
      InstanceType: !Ref InstanceType
      IamInstanceProfile: 'ec2-ssm-core'
      SecurityGroupIds: [!Ref SecurityGroup]             ④
      SubnetId: !Ref Subnet
Outputs:
  InstanceId:                                            ⑤
    Value: !Ref VM
    Description: 'Instance id (connect via Session Manager)'
```

① You'll learn about this in chapter 5.

② The user defines the instance type.

③ Defines a minimal EC2 instance

④ By referencing the security group, an implicit dependency is declared.

⑤ Returns the ID of the EC2 instance

You can find the full code for the template at /chapter04/virtualmachine.yaml in the book's code folder. Please don't worry about VPC, subnets, and security groups at the moment; you'll get to know them in chapter 5.

Where is the template located?

You can find the template on GitHub. You can download a snapshot of the repository at https://github.com/AWSinAction/code3/archive/main.zip. The file we're talking about is named chapter04/virtualmachine.yaml. On S3, the same file is located at https://s3.amazonaws.com/awsinaction-code3/chapter04/virtualmachine.yaml.

If you create an infrastructure from a template, CloudFormation calls it a *stack*. You can think of *template* versus *stack* much like *class* versus *object*. The template exists only once, whereas many stacks can be