```
RouteTableAssociationPublicProxy:                    ④
  Type: 'AWS::EC2::SubnetRouteTableAssociation'
  Properties:
    SubnetId: !Ref SubnetPublicProxy
    RouteTableId: !Ref RouteTablePublicProxy
RoutePublicProxyToInternet:
  Type: 'AWS::EC2::Route'
  Properties:
    RouteTableId: !Ref RouteTablePublicProxy
    DestinationCidrBlock: '0.0.0.0/0'                ⑤
    GatewayId: !Ref InternetGateway
  DependsOn: VPCGatewayAttachment
NetworkAclPublicProxy:                               ⑥
  Type: 'AWS::EC2::NetworkAcl'
  Properties:
    VpcId: !Ref VPC
SubnetNetworkAclAssociationPublicProxy:              ⑦
  Type: 'AWS::EC2::SubnetNetworkAclAssociation'
  Properties:
    SubnetId: !Ref SubnetPublicProxy
    NetworkAclId: !Ref NetworkAclPublicProxy
```

① Picks the first availability zone in the region. (You'll learn about availability zones in chapter 16.)

② IP address space

③ Route table

④ Associates the route table with the subnet

⑤ Routes everything (0.0.0.0/0) to the IGW

⑥ Network access control list (NACL)

⑦ Associates the NACL with the subnet

There's an important difference between security groups and NACLs: security groups are stateful, but NACLs aren't. If you allow an inbound port on a security group, the corresponding response to requests on that port are allowed as well. A security group rule will work as you expect it to. If you open inbound port 80 on a security group, you can connect via HTTP.

That's not true for NACLs. If you open inbound port 80 on an NACL for your subnet, you still may not be able to connect via HTTP. In