addition, you need to allow outbound ephemeral ports, because the web server accepts connections on port 80 but uses an ephemeral port for communication with the client. Ephemeral ports are selected from the range starting at 1024 and ending at 65535. If you want to make an HTTP connection from within your subnet, you have to open outbound port 80 and inbound ephemeral ports as well.

Another difference between security group rules and NACL rules is that you have to define the priority for NACL rules. A smaller rule number indicates a higher priority. When evaluating an NACL, the first rule that matches a package is applied; all other rules are skipped.

The proxy subnet allows clients sending HTTP requests on port 80. The following NACL rules are needed:

- Allow inbound port 80 (HTTP) from 0.0.0.0/0.
- Allow outbound ephemeral ports to 0.0.0.0/0.

We also want to make HTTP and HTTPS requests from the subnet to the internet. The following NACL rules are needed:

- Allow inbound ephemeral ports from 0.0.0.0/0.
- Allow outbound port 80 (HTTP) to 0.0.0.0/0.
- Allow outbound port 443 (HTTPS) to 0.0.0.0/0.

Find the CloudFormation implementation of the previous NACLs next:

```
NetworkAclEntryInPublicProxyHTTP:                    ①
  Type: 'AWS::EC2::NetworkAclEntry'
  Properties:
    NetworkAclId: !Ref NetworkAclPublicProxy
    RuleNumber: '110'                                ②
    Protocol: '6'
```