```
SecurityGroup:
  Type: 'AWS::EC2::SecurityGroup'
  Properties:
    GroupDescription: 'Allowing all incoming and outgoing traffic.'
    VpcId: !Ref VPC
    SecurityGroupIngress:
    - IpProtocol: '-1'
      FromPort: '-1'
      ToPort: '-1'
      CidrIp: '0.0.0.0/0'
    SecurityGroupEgress:
    - IpProtocol: '-1'
      FromPort: '-1'
      ToPort: '-1'
      CidrIp: '0.0.0.0/0'
Proxy:
  Type: AWS::EC2::Instance
  Properties:
    ImageId: 'ami-061ac2e015473fbe2'
    InstanceType: 't2.micro'
    IamInstanceProfile: 'ec2-ssm-core'
    SecurityGroupIds:
    - !Ref SecurityGroup                ①
    SubnetId: !Ref SubnetPublicProxy    ②
    Tags:
    - Key: Name
      Value: Proxy
    UserData: # [...]
  DependsOn: VPCGatewayAttachment       ③
```

① This security group allows everything.

② Launches in the proxy subnet

③ We need to manually tell CloudFormation about a dependency here. Without the attachment being created, the instance could launch but without access to the internet.

The private backend has a different configuration, as shown next:

```
Backend:
  Type: 'AWS::EC2::Instance'
  Properties:
    ImageId: 'ami-061ac2e015473fbe2'
    InstanceType: 't2.micro'
    IamInstanceProfile: 'ec2-ssm-core'
    SecurityGroupIds:
    - !Ref SecurityGroup
    SubnetId: !Ref SubnetPrivateBackend    ①
```