- `userIdentity`—Who called the AWS API to launch an instance?
- `responseElements`—The response from the AWS API when launching an instance. This includes the ID of the launched EC2 instance; we will need to add a tag to the instance later.

Listing 6.1 Event generated by CloudTrail when launching an EC2 instance

```
{
  "version": "0",
  "id": "2db486ef-6775-de10-1472-ecc242928abe",
  "detail-type": "AWS API Call via CloudTrail",                    ①
  "source": "aws.ec2",                                             ②
  "account": "XXXXXXXXXXXX",
  "time": "2022-02-03T11:42:25Z",
  "region": "us-east-1",
  "resources": [],
  "detail": {
    "eventVersion": "1.08",
    "userIdentity": {                                              ③
      "type": "IAMUser",
      "principalId": "XXXXXXXXXXXX",
      "arn": "arn:aws:iam::XXXXXXXXXXXX:user/myuser",              ④
      "accountId": "XXXXXXXXXXXX",
      "accessKeyId": "XXXXXXXXXXXX",
      "userName": "myuser"
    },
    "eventTime": "2022-02-03T11:42:25Z",
    "eventSource": "ec2.amazonaws.com",
    "eventName": "RunInstances",                                  ⑤
    "awsRegion": "us-east-1",
    "sourceIPAddress": "109.90.107.17",
    "userAgent": "aws-cli/2.4.14 Python/3.9.10 Darwin/21.2.0
          ➥ source/arm64 prompt/off command/ec2.run-instances",
    "requestParameters": {
      [...]
    },
    "responseElements": {                                          ⑥
      "requestId": "d52b86c7-5bf8-4d19-86e8-112e59164b21",
      "reservationId": "r-08131583e8311879d",
      "ownerId": "166876438428",
      "groupSet": {},
      "instancesSet": {
        "items": [
          {
```