```
            "instanceId": "i-07a3c0d78dc1cb505",                ⑦
            "imageId": "ami-01893222c83843146",
            [...]
          }
        ]
      }
    },
    "requestID": "d52b86c7-5bf8-4d19-86e8-112e59164b21",
    "eventID": "8225151b-3a9c-4275-8b37-4a317dfe9ee2",
    "readOnly": false,
    "eventType": "AwsApiCall",
    "managementEvent": true,
    "recipientAccountId": "XXXXXXXXXXXX",
    "eventCategory": "Management",
    "tlsDetails": {
      [...]
    }
  }
}
```

① CloudTrail generated the event.

② Someone sent a call to the AWS API, affecting the EC2 service.

③ Information about the user who launched the EC2 instance

④ ID of the user who launched the EC2 instance

⑤ Event was generated because a RunInstances call (used to launch an EC2 instance) was processed by the AWS API.

⑥ Response of the AWS API when launching the instance

⑦ ID of the launched EC2 instance

A rule consists of an event pattern for selecting events, along with a definition of one or multiple targets. The following pattern selects all events from CloudTrail generated by an AWS API call affecting the EC2 service. The pattern matches four attributes from the event described in the next listing: `source`, `detail-type`, `eventSource`, and `eventName`.

Listing 6.2 The pattern to filter events from CloudTrail

```
{
  "source": [
    "aws.ec2"                    ①
```