You can change this behavior by turning on versioning for a bucket. The following command activates versioning for your bucket. Don't forget to replace `$yourname`:

```
$ aws s3api put-bucket-versioning --bucket awsinaction-$yourname \
➥ --versioning-configuration Status=Enabled
```

If you repeat the previous steps, the first version of object A consisting of data 1 will be accessible even after you add an object with key A and data 2. The following command retrieves all objects and versions:

```
$ aws s3api list-object-versions --bucket awsinaction-$yourname
```

You can now download all versions of an object.

Versioning can be useful for backing up and archiving scenarios. Keep in mind that the size of the bucket you'll have to pay for will grow with every new version.

You no longer need to worry about losing data. S3 is designed for 99.999999999% durability of objects over a year. For instance, when storing 100,000,000,000 objects on S3, you will lose only a single object per year on average.

After you've successfully restored your data from the S3 bucket, it's time to clean up. Execute the following command to remove the S3 bucket containing all the objects from your backup. You'll have to replace `$yourname` with your name to select the right bucket. `rb` removes the bucket; the `force` option deletes every object in the bucket before deleting the bucket itself:

```
$ aws s3 rb --force s3://awsinaction-$yourname
```

Your command should look similar to this one:

```
$ aws s3 rb --force s3://awsinaction-awittig
```

You're finished—you've uploaded and downloaded files to S3 with the help of the CLI.

Removing a bucket causes a `BucketNotEmpty` error