```
      "Action":["s3:GetObject"],                    ③
      "Resource":["arn:aws:s3:::$BucketName/*"]     ④
    }
  ]
}
```

① Allows access...

② ...for anyone

③ Reads objects

④ Your bucket

You can add a bucket policy to your bucket with the following command. Replace `$BucketName` with the name of your bucket and `$pathToPolicy` with the path to the bucketpolicy.json file:

```
$ aws s3api put-bucket-policy --bucket $BucketName \
➥ --policy file://$pathToPolicy/bucketpolicy.json
```

Every object in the bucket can now be downloaded by anyone. You need to enable and configure the static web-hosting feature of S3 next. To do so, execute the following command, replacing `$BucketName` with the name of your bucket:

```
$ aws s3 website s3://$BucketName --index-document helloworld.xhtml
```

Your bucket is now configured to deliver a static website. The HTML document helloworld.xhtml is used as index page. You'll learn how to access your website next.

7.6.3 Accessing a website hosted on S3

You can now access your static website with a browser. To do so, you need to choose the right endpoint. The endpoints for S3 static web hosting depend on your bucket's region. For us-east-1 (US East N. Virginia), the website endpoint looks like this:

```
http://$BucketName.s3-website-us-east-1.amazonaws.com
```

Replace `$BucketName` with your bucket. So if your bucket is called `awesomebucket` and was created in the default region us-east-1, your bucket