name would be:

```
http://awesomebucket.s3-website-us-east-1.amazonaws.com
```

Open this URL with your browser. You should be welcomed by a Hello World website.

Please note that for some regions, the website endpoint looks a little different. Check S3 endpoints and quotas at http://mng.bz/epeq for details.

Linking a custom domain to an S3 bucket

If you want to avoid hosting static content under a domain like awsinaction.s3-website-us-east-1.amazonaws.com, you can link a custom domain to an S3 bucket, such as `awsinaction.example.com`. All you have to do is to add a CNAME record for your domain, pointing to the bucket's S3 endpoint. The domain name system provided by AWS allowing you to create a CNAME record is called Route 53.

The CNAME record will work only if you comply with the following rules:

- *Your bucket name must match the CNAME record name.* For example, if you want to create a CNAME for awsinaction.example.com, your bucket name must be awsinaction.example.com as well.
- *CNAME records won't work for the primary domain name (such as* example.com*)*. You need to use a subdomain for CNAMEs like awsinaction or www. If you want to link a primary domain name to an S3 bucket, you need to use the Route 53 DNS service from AWS.

Linking a custom domain to your S3 bucket works only for HTTP. If you want to use HTTPS (and you probably should), use AWS CloudFront together with S3. AWS CloudFront accepts HTTPS from the client and forwards the request to S3.



Cleaning up

Don't forget to clean up your bucket after you finish the example. To do so, execute the following command, replacing `$BucketName` with the name of your bucket: