```
$ sudo mkfs -t xfs /dev/xvdf
meta-data=/dev/xvdf              isize=512    agcount=4, agsize=327680 blks
         =                       sectsz=512   attr=2, projid32bit=1
         =                       crc=1        finobt=1, sparse=0
data     =                       bsize=4096   blocks=1310720, imaxpct=25
         =                       sunit=0      swidth=0 blks
naming   =version 2              bsize=4096   ascii-ci=0 ftype=1
log      =internal log           bsize=4096   blocks=2560, version=2
         =                       sectsz=512   sunit=0 blks, lazy-count=1
realtime =none                   extsz=4096   blocks=0, rtextents=0
```

After the filesystem has been created, you can mount the device as follows:

```
$ sudo mkdir /data
$ sudo mount /dev/xvdf /data
```

To see mounted volumes, use `df` like this:

```
$ df -h
Filesystem      Size  Used Avail Use% Mounted on
devtmpfs        484M     0  484M   0% /dev
tmpfs           492M     0  492M   0% /dev/shm
tmpfs           492M  348K  491M   1% /run
tmpfs           492M     0  492M   0% /sys/fs/cgroup
/dev/xvda1      8.0G  1.5G  6.6G  19% /                ①
/dev/xvdf       5.0G   38M  5.0G   1% /data            ②
```

① Root volume

② Additional volume

EBS volumes are independent of your virtual machine. To see this in action, as shown in the next code snippet, you will save a file to a volume, unmount, and detach the volume. Afterward, you will attach and mount the volume again. The data will still be available!

```
$ sudo touch /data/testfile    ①
$ sudo umount /data            ②
```