To restore a snapshot, you must create a new EBS volume based on that snapshot. Execute the following command in your terminal, replacing `$SnapshotId` with the ID of your snapshot:

```
$ aws ec2 create-volume --snapshot-id $SnapshotId \     ①
➥ --availability-zone us-east-1a                       ②
{
    "AvailabilityZone": "us-east-1a",
    "CreateTime": "2022-08-25T08:08:49+00:00",
    "Encrypted": false,
    "Size": 5,
    "SnapshotId": "snap-0babfe807decdb918",
    "State": "creating",
    "VolumeId": "vol-0bf4fdf3816f968c5",                ③
    "Iops": 100,
    "Tags": [],
    "VolumeType": "gp2",
    "MultiAttachEnabled": false
}
```

① The ID of your snapshot used to create the volume

② Choose data center.

③ The $RestoreVolumeId of the volume restored from your snapshot



Cleaning up

Don’t forget to delete the snapshot, the volume, and your stack. The following code will delete the snapshot and volume. Don’t forget to replace `$SnapshotId` with the ID of the EBS snapshot you created earlier and `$RestoreVolumeId` with the ID of the EBS volume you created by restoring the snapshot:

```
$ aws ec2 delete-snapshot --snapshot-id $SnapshotId
$ aws ec2 delete-volume --volume-id $RestoreVolumeId
```

Also delete your CloudFormation stack named `ebs` after you finish this section to clean up all used resources as follows: