```
      - Key: Name
        Value: 'efs-a'
    CreationPolicy:
      ResourceSignal:
        Timeout: PT10M
    DependsOn:
    - VPCGatewayAttachment
    - MountTargetA
```

① Creates an EC2 instance

② The IAM role grants access to the EFS filesystem (see the next listing).

③ Attaches the security group, which is used to identify outgoing traffic to the filesystem

④ Places the EC2 instance into subnet A

⑤ Adds a Bash script to the user data of the virtual machine, which is executed automatically at the end of the first boot process

⑥ Backs up all home directories to /oldhome

⑦ After creating a new filesystem, it takes a few minutes until its DNS name resolves to the mount targets.

⑧ Adds an entry to fstab, which makes sure the filesystem is mounted automatically on each boot

⑨ Mounts all entries—most importantly the EFS filesystem—defined in fstab without the need of rebooting the system

⑩ Copies the old home directories to the EFS filesystem mounted under /home

Sends a success signal to CloudFormation

Tells CloudFormation to wait until it receives a success signal from the EC2 instance

The EC2 instance requires internet connectivity as well as a mount target. Because both dependencies are not apparent to CloudFormation, we add them manually here.

To prove that the EFS filesystem allows you to share files across multiple instances, we are adding a second EC2 instance, as shown next.

Listing 9.5 Mounting an EFS filesystem from a second EC2 instance

```
Resources:
  [...]
  EC2InstanceB:
    Type: 'AWS::EC2::Instance'
```