```
    Properties:
      ImageId: !FindInMap [RegionMap, !Ref 'AWS::Region', AMI]
      InstanceType: 't2.micro'
      IamInstanceProfile: !Ref IamInstanceProfile
      NetworkInterfaces:
      - AssociatePublicIpAddress: true
        DeleteOnTermination: true
        DeviceIndex: 0
        GroupSet:
        - !Ref EFSClientSecurityGroup
        SubnetId: !Ref SubnetB                ①
      UserData:
        'Fn::Base64': !Sub |
          #!/bin/bash -ex
          trap '/opt/aws/bin/cfn-signal -e 1 --stack ${AWS::StackName}
➥ --resource EC2InstanceB --region ${AWS::Region}' ERR

          # install dependencies
          yum install -y nc amazon-efs-utils
          pip3 install botocore               ②

          # wait for EFS mount target
          while ! (echo > /dev/tcp/${FileSystem}.efs.${AWS::Region}
➥ .amazonaws.com/2049) >/dev/null 2>&1; do sleep 5; done

          # mount EFS filesystem
          echo "${FileSystem}:/ /home efs _netdev,noresvport,tls,iam 0 0"
➥ >> /etc/fstab
          mount -a

          /opt/aws/bin/cfn-signal -e $? --stack ${AWS::StackName}
➥ --resource EC2InstanceB --region ${AWS::Region}
      Tags:
      - Key: Name
        Value: 'efs-b'
    CreationPolicy:
      ResourceSignal:
        Timeout: PT10M
    DependsOn:
    - VPCGatewayAttachment
    - MountTargetB
```

① Places the EC2 instance into subnet B

② The old /home folder is not copied here. This is already done on the first EC2 instance in subnet A.

To make things easier, you can also add outputs to the template to expose the IDs of your EC2 instances like this: