```
$ aws rds restore-db-instance-to-point-in-time \
➥ --target-db-instance-identifier awsinaction-db-restore-time \
➥ --source-db-instance-identifier $DBInstanceIdentifier \
➥ --restore-time $Time --db-subnet-group-name $SubnetGroup
```

A new database named awsinaction-db-restore-time is created based on the source database from five minutes ago. In theory, after the database is created, you could switch the WordPress application to the new endpoint by modifying the /var/www/ html/wp-config.php file on both virtual machines.

10.3.4 Copying a database to another region

When you created the cloud infrastructure for WordPress, you assumed that most readers will come from the United States. It turns out, however, that most readers access your site from Europe. Therefore, you decide to move your cloud infrastructure to reduce latency for the majority of your readers.

Copying a database to another region is possible with the help of snapshots as well. The main reasons you might do so follow:

- *Disaster recovery*—You can recover from an unlikely region-wide outage.
- *Relocating*—You can move your infrastructure to another region so you can serve your customers with lower latency.

The second command copies the snapshot named `wordpress-manual-snapshot` from the region `us-east-1` to the region `eu-west-1`. You need to replace `$SourceSnapshotArn` with the Amazon Resource Name (ARN) of the snapshot. Use the following command to get the ARN of your manual snapshot: