```
$ aws rds describe-db-snapshots \
➥ --db-snapshot-identifier wordpress-manual-snapshot \
➥ --query "DBSnapshots[0].DBSnapshotArn" --output text
```

COMPLIANCE Moving data from one region to another may violate privacy laws or compliance rules. Make sure you're allowed to copy the data to another region if you're working with real data.

```
$ aws rds copy-db-snapshot \
➥ --source-db-snapshot-identifier $SourceSnapshotArn \
➥ --target-db-snapshot-identifier wordpress-manual-snapshot \
➥ --region eu-west-1
```

After the snapshot has been copied to the region `eu-west-1`, you can restore a database from it as described in the previous section.

10.3.5 Calculating the cost of snapshots

Snapshots are billed based on the storage they use. You can store snapshots up to the size of your database instance for free. In our WordPress example, you can store up to 5 GB of snapshots for free. On top of that, you pay per GB per month of used storage. As we're writing this book, the cost is $0.095 for each GB every month.



Cleaning up

It's time to clean up the snapshots and delete the restored database instances. Execute the following commands step by step, or jump to the shortcuts for Linux and macOS after the listing:

```
$ aws rds delete-db-instance --db-instance-identifier \
➥ awsinaction-db-restore --skip-final-snapshot                ①
$ aws rds delete-db-instance --db-instance-identifier \
```