```
➥ awsinaction-db-restore-time --skip-final-snapshot          ②
$ aws rds delete-db-snapshot --db-snapshot-identifier \
➥ wordpress-manual-snapshot                                  ③
$ aws rds delete-db-snapshot --db-snapshot-identifier \
➥ wordpress-copy-snapshot                                    ④
$ aws --region eu-west-1 rds delete-db-snapshot --db-snapshot-
identifier \
➥ wordpress-manual-snapshot                                  ⑤
```

① Deletes the database with data from the snapshot restore

② Deletes the database with data from the point-in-time restore

③ Deletes the manual snapshot

④ Deletes the copied snapshot

⑤ Deletes the snapshot copied to another region

You can avoid typing these commands manually at your terminal by using the following command to download a bash script and execute it directly on your local machine. The bash script contains the same steps as shown in the previous snippet:

```
$ curl -s https:/ /raw.githubusercontent.com/AWSinAction/\
➥ code3/main/chapter10/cleanup.sh | bash -ex
```

Keep the rest of the setup, because you'll use it in the following sections.

10.4 Controlling access to a database

Every day, you can read about WordPress sites that got hacked. One essential aspect of protecting your WordPress site is controlling access to your cloud infrastructure and database.

The shared-responsibility model applies to the RDS service as well as to AWS services in general. AWS is responsible for the security of the cloud in this case—for example, for the security of the underlying