```
    DBInstanceClass: 'db.m3.large'       ①
    DBName: wordpress
    Engine: MySQL
    MasterUsername: wordpress
    MasterUserPassword: wordpress
    VPCSecurityGroups:
    - !Sub ${DatabaseSecurityGroup.GroupId}
    DBSubnetGroupName: !Ref DBSubnetGroup
    MultiAZ: true
  DependsOn: VPCGatewayAttachment
```

① Increases the size of the underlying virtual machine for the database instance from db.t2.micro to db.m3.large

Because a database has to read and write data to a disk, I/O performance is important for the database's overall performance. RDS offers the following three different types of storage, as you already know from reading about the block storage service EBS:

- General purpose (SSD)
- Provisioned IOPS (SSD)
- Magnetic

You should choose general-purpose (SSD) or even provisioned IOPS (SSD) storage for production workloads. The options are exactly the same as when using EBS for virtual machines. If you need to guarantee a high level of read or write throughput, you should use provisioned IOPS (SSD). The general-purpose (SSD) option offers moderate baseline performance with the ability to burst. The throughput for general purpose (SSD) depends on the amount of initialized storage size. Magnetic storage is an option if you need to store data at a low cost, or if you don't need to access it in a predictable, performant way. The next listing shows how to enable general-purpose (SSD) storage using a CloudFormation template.