As mentioned already, ElastiCache nodes in a cluster use only private IP addresses. Therefore, you can't connect to a node directly over the internet. The same is true for other resources as RDS database instances. Therefore, create an EC2 instance in the same VPC as the cluster for testing. From the EC2 instance, you can then connect to the private IP address of the cluster.

11.1.2 Test the Redis cluster

To be able to access the ElastiCache cluster, you'll need a virtual machine. The following snippet shows the required resources:

```
Resources:
  # [...]
  InstanceSecurityGroup:                                    ①
    Type: 'AWS::EC2::SecurityGroup'
    Properties:
      GroupDescription: 'vm'
      VpcId: !Ref VPC
  Instance:                                                 ②
    Type: 'AWS::EC2::Instance'
    Properties:
      ImageId: !FindInMap [RegionMap, !Ref 'AWS::Region', AMI]
      InstanceType: 't2.micro'
      IamInstanceProfile: !Ref InstanceProfile
      NetworkInterfaces:
      - AssociatePublicIpAddress: true
        DeleteOnTermination: true
        DeviceIndex: 0
        GroupSet:
        - !Ref InstanceSecurityGroup
        SubnetId: !Ref SubnetA
Outputs:
  InstanceId:                                               ③
    Value: !Ref Instance
    Description: 'EC2 Instance ID (connect via Session Manager)'
  CacheAddress:                                             ④
    Value: !GetAtt 'Cache.RedisEndpoint.Address'
    Description: 'Redis DNS name (resolves to a private IP address)'
```

① The security group does allow outbound traffic only.

② The virtual machine used to connect to your Redis cluster

③ The ID of the instance used to connect via the Session Manager

④ The DNS name of Redis cluster node (resolves to a private IP address)

Next, create a stack based on the template to create all the resources in your AWS account using the Management Console: http://mng.bz/09jm. You have to fill in the next three parameters when creating the stack: