- `SubnetA`—You should have at least two options here; select the first one.
- `SubnetB`—You should have at least two options here; select the second one.
- `VPC`—You should have only one possible VPC here—your default VPC. Select it.

Want to have a deeper look into the CloudFormation template?

Where is the template located?

You can find the template on GitHub. Download a snapshot of the repository at https://github.com/AWSinAction/code3/archive/main.zip. The file we're talking about is located at chapter11/redis-minimal.yaml. On S3, the same file is located at http://mng.bz/9Vra.

The following example guides you through storing a gamer's session, as well as populating and reading a highscore list:

1. Wait until the CloudFormation stack reaches status `CREATE_COMPLETE`.
2. Select the stack and open the Outputs tab. Copy the EC2 instance ID and cache address.
3. Use the Session Manager to connect to the EC2 instance, and use the Redis CLI to interact with the Redis cluster node as described in the following listing.
4. Execute the following commands. Don't forget to replace `$CacheAddress` with the value from the CloudFormation outputs:

```
$ sudo amazon-linux-extras install -y redis6    ①
$ redis-cli -h $CacheAddress                    ②
> SET session:gamer1 online EX 15               ③
OK
> GET session:gamer1                            ④
"online"
> GET session:gamer1                            ⑤
(nil)                                           ⑥
> ZADD highscore 100 "gamer1"                   ⑦
(integer) 1
> ZADD highscore 50 "gamer2"                    ⑧
(integer) 1
> ZADD highscore 150 "gamer3"                   ⑨
(integer) 1
> ZADD highscore 5 "gamer4"                     ⑩
(integer) 1
```