Usually, high eviction rates are a sign that you either aren't using a TTL to expire keys after some time or that your cache is too small. You can solve this issue by increasing the memory of the cache, either by increasing the node type or by adding more shards. You might set an alarm to trigger if the 10-minute average of the `Evictions` metric is higher than 1000 for one out of one data points.

11.5.3 Is my Redis replication up-to-date?

The `ReplicationLag` metric is applicable only for a node running as a read replica. It represents how far behind, in seconds, the replica is in applying changes from the primary node. The higher this value, the more out of date the replica is. This can be a problem because some users of your application will see very old data. In the gaming application, imagine you have one primary node and one replica node. All reads are performed by either the primary or the replica node. The `ReplicationLag` is 600, which means that the replication node looks like the primary node looked 10 minutes before. Depending on which node the user hits when accessing the application, they could see 10-minute-old data.

What are reasons for a high `ReplicationLag`? There could be a problem with the sizing of your cluster—for example, your cache cluster might be at capacity. Typically this will be a sign to increase the capacity by adding shards or replicas. You might set an alarm to trigger if the 10-minute average of the `ReplicationLag` metric is higher than 30 for one consecutive period.



Cleaning up

It's time to delete the running CloudFormation stack, as shown here:

```
$ aws cloudformation delete-stack --stack-name discourse
```

11.6 Tweaking cache performance

Your cache can become a bottleneck if it can no longer handle the requests with low latency. In the previous section, you learned how to monitor your cache. In this