```
    Item: {
      uid: {S: input['<uid>']},
      tid: {N: tid.toString()},                          ②
      description: {S: input['<description>']},
      created: {N: moment(tid).format('YYYYMMDD')}       ③
    },
    TableName: 'todo-task',                              ④
    ConditionExpression: 'attribute_not_exists(uid)
➥ and attribute_not_exists(tid)'                        ⑤
  };
  if (input['--dueat'] !== null) {                       ⑥
    params.Item.due = {N: input['--dueat']};
  }
  if (input['<category>'] !== null) {                    ⑦
    params.Item.category = {S: input['<category>']};
  }
  db.putItem(params, (err) => {                          ⑧
    if (err) {
      console.error('error', err);
    } else {
      console.log('task added with tid ' + tid);
    }
  });
}
```

① Creates the task ID (tid) based on the current timestamp

② The tid attribute is of type number and contains the tid value.

③ The created attribute is of type number (format 20150525).

④ Specifies the task table

⑤ Ensures that an existing item is not overridden

⑥ If the optional named parameter dueat is set, adds this value to the item

⑦ If the optional named parameter category is set, adds this value to the item

⑧ Invokes the putItem operation on DynamoDB

Now we'll add some tasks. Use the following command to remind Emma about buying some milk and a task asking John to put out the garbage:

```
node index.js task-add emma "buy milk" "shopping"
node index.js task-add emma "put out the garbage" "housekeeping" --dueat "20220224"
```