```
  "34.236.255.218",          ②
  "172.31.37.225",           ③
  "subnet-0997e66d"          ④
]
```

① Instance ID of the virtual machine

② Public IP address of the virtual machine

③ Private IP address of the virtual machine

④ Subnet ID of the virtual machine

Next, create a new Jenkins job by following these steps:

1. Open http://$PublicIP:8080/newJob in your browser, and replace `$PublicIP` with the public IP address from the output of the previous `describe` command.
2. Log in with user `admin` and the password you chose when starting the CloudFormation template.
3. Select the Install Suggested Plugins option.
4. Keep the default for Jenkins URL and click Save and Finish.
5. Click Start Using Jenkins.
6. Click New Item to create a new project.
7. Type in AWS in Action as the name for the new project.
8. Select Freestyle Project as the job type, and click OK.

You've made some changes to the state of Jenkins stored on EFS. Now terminate the EC2 instance with the following command, and you will see that Jenkins recovers from the failure without data loss. Replace `$InstanceId` with the instance ID from the output of the previous `describe` command:

```
$ aws ec2 terminate-instances --instance-ids $InstanceId
```

After a few minutes, the Auto Scaling group detects that the virtual machine was terminated and starts a new virtual machine. Rerun the `describe-instances` command shown next until the output contains a new running virtual machine:

```
$ aws ec2 describe-instances --filters "Name=tag:Name,\
➥ Values=jenkins-multiaz-efs" "Name=instance-state-code,Values=16" \
➥ --query "Reservations[0].Instances[0].\
```