```
➥ [InstanceId, PublicIpAddress, PrivateIpAddress, SubnetId]"
[
  "i-07ce0865adf50cccf",
  "34.200.225.247",
  "172.31.37.199",
  "subnet-0997e66d"
]
```

The instance ID, the public IP address, the private IP address, and probably even the subnet ID have changed for the new instance. Open http://$PublicIP:8080 in your browser, and replace `$PublicIP` with the public IP address from the output of the previous `describe-instances` command. The web interface from the Jenkins server appears, and it still contains the AWS in Action job you created recently.

You've now built a highly available architecture consisting of an EC2 instance with the help of autoscaling. State is now stored on EFS and is no longer lost when an EC2 instance is replaced. There is one problem left: the public and private IP addresses of the Jenkins server change after a new virtual machine is started for recovery. The Jenkins server is no longer available under the same endpoint.



Cleaning up

It's time to clean up to avoid unwanted costs. Execute the following command to delete all resources corresponding to the Jenkins setup:

```
$ aws cloudformation delete-stack --stack-name jenkins-multiaz-efs
$ aws cloudformation wait stack-delete-complete \
➥ --stack-name jenkins-multiaz-efs         ①
```

① Waits until the stack is deleted

You'll learn how to solve the last problem next.