```
$ aws ec2 describe-availability-zones --region $Region  ①
{
  "AvailabilityZones": [
    {
      "State": "available",
      "OptInStatus": "opt-in-not-required",
      "Messages": [],
      "RegionName": "us-east-1",                        ②
      "ZoneName": "us-east-1a",                         ③
      "ZoneId": "use1-az1",                             ④
      "GroupName": "us-east-1",
      "NetworkBorderGroup": "us-east-1",
      "ZoneType": "availability-zone"
    },
    {
      "State": "available",
      "OptInStatus": "opt-in-not-required",
      "Messages": [],
      "RegionName": "us-east-1",
      "ZoneName": "us-east-1b",
      "ZoneId": "use1-az2",
      "GroupName": "us-east-1",
      "NetworkBorderGroup": "us-east-1",
      "ZoneType": "availability-zone"
    },
    [...]
    {
      "State": "available",
      "OptInStatus": "opt-in-not-required",
      "Messages": [],
      "RegionName": "us-east-1",
      "ZoneName": "us-east-1f",
      "ZoneId": "use1-az5",
      "GroupName": "us-east-1",
      "NetworkBorderGroup": "us-east-1",
      "ZoneType": "availability-zone"
    }
  ]
}
```

① Lists the availability zones of a region

② The region name

③ The name of the availability zone might point to different data centers in different AWS accounts.

④ The ID of the availability zone points to the same data centers in all AWS accounts.

At the end of the chapter, you will learn how to analyze resilience requirements and derive an AWS architecture from the results.