```
    Bucket: config.Bucket,                          ④
    Key: `${body.id}.png`,                          ⑤
    Body: screenshot,
    ContentType: 'image/png',                       ⑥
    ACL: 'public-read',                             ⑦
  }).promise();

  await browser.close();
};
```

① The message body is a JSON string. You convert it back into a JavaScript object.

② Launches a headless browser

③ Takes a screenshot

④ The S3 bucket to which to upload the image

⑤ The key, consisting of the random ID generated by the client and included in the SQS message

⑥ Sets the content type to make sure browsers are showing the image correctly

⑦ Allows anyone to read the image from S3 (public access)

The only step that's missing is to acknowledge that the message was successfully consumed, as shown in the next listing. This is done by deleting the message from the queue after successfully completing the task. If you receive a message from SQS, you get a `ReceiptHandle`, which is a unique ID that you need to specify when you delete a message from a queue.

Listing 14.7 worker.js: Acknowledging a message (deletes the message from the queue)

```
async function acknowledge(message) {
  await sqs.deleteMessage({                         ①
    QueueUrl: config.QueueUrl,
    ReceiptHandle: message.ReceiptHandle            ②
  }).promise();
};
```

① Invokes the deleteMessage operation on SQS

② ReceiptHandle is unique for each receipt of a message.