```
# [...]
ArtifactBucket:                                                    ①
  Type: 'AWS::S3::Bucket'
  Properties: {}
Application:                                                       ②
  Type: 'AWS::CodeDeploy::Application'
  Properties:
    ApplicationName: 'etherpad-codedeploy'
    ComputePlatform: 'Server'
DeploymentGroup:                                                   ③
  Type: 'AWS::CodeDeploy::DeploymentGroup'
  Properties:
    ApplicationName: !Ref Application
    DeploymentGroupName: 'etherpad-codedeploy'
    AutoScalingGroups:                                             ④
    - !Ref AutoScalingGroup
    DeploymentConfigName: 'CodeDeployDefault.AllAtOnce'            ⑤
    LoadBalancerInfo:                                              ⑥
      TargetGroupInfoList:
      - Name: !GetAtt LoadBalancerTargetGroup.TargetGroupName
    ServiceRoleArn: !GetAtt CodeDeployRole.Arn                     ⑦
CodeDeployRole:                                                    ⑧
  Type: 'AWS::IAM::Role'
  Properties:
    AssumeRolePolicyDocument:
      Version: '2012-10-17'
      Statement:
      - Effect: Allow
        Principal:
          Service: 'codedeploy.amazonaws.com'
        Action: 'sts:AssumeRole'
    ManagedPolicyArns:
    - 'arn:aws:iam::aws:policy/service-role/AWSCodeDeployRole'
DatabaseHostParameter:                                             ⑨
  Type: 'AWS::SSM::Parameter'
  Properties:
    Name: '/etherpad-codedeploy/database_host'
    Type: 'String'
    Value: !GetAtt 'Database.Endpoint.Address'
# [...]
```

① The S3 bucket to store the deployment artifacts

② The CodeDeploy application—a collection of deployment groups and revisions

③ The CodeDeploy deployment group specifies the targets for a deployment.

④ The deployment group points to the Auto Scaling group.