```
[
  {
    "OutputKey": "ArtifactBucket",
    "OutputValue": "etherpad-codedeploy-artifactbucket-12vah1x44tpg7",    ①
    "Description": "Name of the artifact bucket"
  },
  {
    "OutputKey": "URL",
    "OutputValue": "http://ether-LoadB-...us-east-1.elb.amazonaws.com",  ②
    "Description": "The URL of the Etherpad application"
  }
]
```

① Copies the name of the S3 bucket used to store the deployment artifacts

② Opens the URL in your browser to access Etherpad

Note the `ArtifactBucket` output. You will need the name of the S3 bucket in the following step. Also, open the `URL` output in your browser. The ALB shows an error page, because you haven't deployed the application yet.

Creating a deployment artifact, also called a revision, is the next step. To do so, you need to create a zip file containing the source code, the scripts, and a configuration file. You'll find an example to deploy Etherpad in the book's code repository on GitHub: https://github.com/AWSinAction/code3 at /chapter15/etherpad-lite-1.8.17.zip. We encourage you to unzip the file to take a closer look at its contents.

The deployment instruction file needed for CodeDeploy is called an AppSpec file: appspec.yml. The following listing explains the AppSpec file that we prepared to deploy Etherpad.

Listing 15.2 The AppSpec file used to deploy Etherpad with the help of CodeDeploy