```
version: 0.0                                    ①
os: linux                                       ②
files:                                          ③
- source: .
  destination: /etherpad
hooks:                                          ④
  BeforeInstall:                                ⑤
  - location: hook_before_install.sh
    timeout: 60
  AfterInstall:                                 ⑥
  - location: hook_after_install.sh
    timeout: 60
  ApplicationStart:                             ⑦
  - location: hook_application_start.sh
    timeout: 180
    runas: ec2-user
  ValidateService:                              ⑧
  - location: hook_validate_service.sh
    timeout: 300
    runas: ec2-user
```

① Odd but true: the latest version of the App Spec file format is 0.0.

② CodeDeploy supports Linux and Windows.

③ Copies all files from the archive to /etherpad

④ Hooks allow you to run scripts during the deployment process.

⑤ Triggered before CodeDeploy copies the source files

⑥ Triggered after CodeDeploy copies the source files

⑦ Triggered to start the application

⑧ Triggered to validate the service after starting the application

Now let's inspect the contents of the `hook_after_install.sh` script in the next listing.

Listing 15.3 Executing the script after the install step

```
#!/bin/bash -ex

TOKEN=`curl -X PUT "http://169.254.169.254/
➥ latest/api/token"                                    ①
➥ -H "X-aws-ec2-metadata-token-ttl-seconds: 60"`
```