Open the URL in your browser, and create a pad. Click the settings icon to check the current version of Etherpad as you did in the previous section. The version is `c85ab49`, which is the latest Git commit ID for version 1.8.17.

Great, but how did we deploy Etherpad to the EC2 instance? The following listing shows the CloudFormation template chapter15/cloudformation.yaml and answers this question.

Listing 15.4 Adding a bash script to the user data

```
# [...]
LaunchTemplate:                                                    ①
  Type: 'AWS::EC2::LaunchTemplate'
  Properties:
    LaunchTemplateData:
      # [...]
      ImageId: !FindInMap [RegionMap,
➥ !Ref 'AWS::Region', AMI]                                        ②
      InstanceType: 't2.micro'                                     ③
      UserData:                                                    ④
        'Fn::Base64': !Sub |
          #!/bin/bash -ex                                          ⑤
          trap '/opt/aws/bin/cfn-signal -e 1 --stack ${AWS::StackName}
➥ --resource AutoScalingGroup --region ${AWS::Region}' ERR        ⑥

          # Install nodejs and git
          curl -fsSL https:/ /rpm.nodesource.com/setup_14.x | bash -
          yum install -y nodejs git

          # Fetch, configure, and start Etherpad as non-root user
          su ec2-user -c '
          cd /home/ec2-user/
          git clone --depth 1 --branch ${EtherpadVersion}
➥ https:/ /github.com/AWSinAction/etherpad-lite.git              ⑦
          cd etherpad-lite/
          echo "
          {
            \"title\": \"Etherpad\",
            \"dbType\": \"mysql\",
            \"dbSettings\": {
              \"host\": \"${Database.Endpoint.Address}\",
              \"port\": \"3306\",
```