③ The region used to build the AMI

④ The source filter defines the base AMI from which to start.

⑤ Searches for Amazon Linux 2 images; the * represents all versions.

⑥ Picks the latest version of the Amazon Linux 2 images

⑦ Filters only AMIs owned by Amazon; the AWS account 137112412989 belongs to Amazon.

⑧ Tells Packer to use the Session Manager instead of plain SSH to connect with the temporary build instance

⑨ Attaches the IAM instance profile ec2-ssm-core, which is required for the Session Manager

⑩ Adds regions to distribute the AMI worldwide

The last part of the Packer template is shown in the next listing. In the build step, a shell provisioner is used to execute commands on the temporary build instance.

Listing 15.8 The Packer template to build an Etherpad AMI, part 3

```
build {
  name    = "awsinaction-etherpad"
  sources = [
    "source.amazon-ebs.etherpad"                          ①
  ]

  provisioner "shell" {                                   ②
    inline = [
      "curl -fsSL https:/ /rpm.nodesource.com/setup_14.x
➥ | sudo bash -",                                        ③
      "sudo yum install -y nodejs git",                   ④
      "sudo mkdir /opt/etherpad-lite",
      "sudo chown -R ec2-user:ec2-user /opt/etherpad-lite",
      "cd /opt",
      "git clone --depth 1 --branch 1.8.17 https:/ /github.com/
➥ AWSinAction/etherpad-lite.git",                        ⑤
      "cd etherpad-lite",
      "./src/bin/installDeps.sh",                         ⑥
    ]
  }
}
```