Listing 16.7 explains the configuration file we used to build the AMIs for you. Please note: you do not need to run Packer to build your own AMIs. We have done so already and shared the AMIs publicly.

Find the Packer configuration file at chapter16/imagery.pkr.hcl in our source code repository at https://github.com/AWSinAction/code3.

Listing 16.7 Configuring Packer to build an AMI containing the Imagery app

```
packer {                                                                    ①
  required_plugins {
    amazon = {                                                              ②
      version = ">= 0.0.2"
      source  = "github.com/hashicorp/amazon"
    }
  }
}

source "amazon-ebs" "imagery" {                                             ③
  ami_name      = "awsinaction-imagery-{{timestamp}}"                       ④
  tags = {                                                                  ⑤
    Name = "awsinaction-imagery"
  }
  instance_type = "t2.micro"                                                ⑥
  region        = "us-east-1"                                               ⑦
  source_ami_filter {                                                       ⑧
    filters = {
      name                = "amzn2-ami-hvm-2.0.*-x86_64-gp2"
      root-device-type    = "ebs"
      virtualization-type = "hvm"
    }
    most_recent = true
    owners      = ["137112412989"]
  }
  ssh_username = "ec2-user"                                                 ⑨
  ami_groups = ["all"]                                                      ⑩
  ami_regions = [
    "us-east-1",
    # [...]
  ]
}
```