```
build {
  name    = "awsinaction-imagery"
  sources = [
    "source.amazon-ebs.imagery"
  ]

  provisioner "file" {
    source = "./"
    destination = "/home/ec2-user/"
  }

  provisioner "shell" {
    inline = [
      "curl -sL https:/ /rpm.nodesource.com/setup_14.x | sudo bash -",
      "sudo yum update",
      "sudo yum install -y nodejs cairo-devel
➥ libjpeg-turbo-devel",
      "cd server/ && npm install && cd -",
      "cd worker/ && npm install && cd -"
    ]
  }
}
```

① Initializes and configures Packer

② Adds the plug-in required to build AMIs

③ Configures how Packer will create the AMI

④ The name for the AMI created by Packer

⑤ The tags for the AMI created by Packer

⑥ The instance type used by Packer when spinning up a virtual machine to build the AMI

⑦ The region used by Packer to create the AMI

⑧ The filter describes how to find the base AMI—the latest version of Amazon Linux 2—from which to start.

⑨ The username required to connect to the build instance via SSH

⑩ Allows anyone to access the AMI

Copies the AMI to all commercial regions

Configures the steps Packer executes while building the image

The name for the build

The sources for the build (references source from above)

Copies all files and folders from the current directory ...

... to the home directory of the EC2 instance used to build the AMI