In some cases, scaling based on CPU usage, request count per target, or network throughput does not work. For example, you might have another bottleneck you need to scale on, such as disk I/O. Any CloudWatch metric can be used for target tracking as well. Only one requirement exists: adding or removing instances must affect the metric proportionally. For example, request latency is not a valid metric for target tracking, because adjusting the number of instances does not affect the request latency directly.

The following listing shows a target-tracking policy based on the average CPU utilization of all EC2 instances of the Auto Scaling group.

Listing 17.6 Creating a scalable, HA WordPress setup, part 3

```
ScalingPolicy:
  Type: 'AWS::AutoScaling::ScalingPolicy'                    ①
  Properties:
    AutoScalingGroupName: !Ref AutoScalingGroup              ②
    PolicyType: TargetTrackingScaling                        ③
    TargetTrackingConfiguration:                             ④
      PredefinedMetricSpecification:                         ⑤
        PredefinedMetricType: ASGAverageCPUUtilization       ⑥
      TargetValue: 70                                        ⑦
    EstimatedInstanceWarmup: 60                              ⑧
```

① Creates a scaling policy
② Adjusts the desired capacity of the Auto Scaling group
③ Creates a scaling policy tracking a specified target
④ Configures the target tracking
⑤ Uses a predefined scaling metric
⑥ Average CPU usage across all EC2 instances of the ASG
⑦ Defines the target at 70% CPU usage
⑧ Excludes newly launched EC2 instances from CPU metric for 60 seconds to avoid scaling on load caused due to the bootstrapping of the VM and your application

Follow these steps after the CloudFormation stack reaches the state `CREATE_COMPLETE` to create a new blog post containing an image:

1. Select the CloudFormation stack `wordpress`, and switch to the Outputs tab.
2. Open the link shown for key `URL` with a web browser.
3. Search for the Log In link in the navigation bar, and click it.
4. Log in with username `admin` and the password you specified when creating the stack with the CLI.