You may have noticed that the concepts from the previous chapters can be transferred to a modern architecture based on ECS easily.

As usual, you'll find the code in the book's code repository on GitHub: https://github.com/AWSinAction/code3. The CloudFormation template for the Notea example is located in /chapter18/notea.yaml.

Execute the following command to create a CloudFormation stack that spins up Notea. Don't forget to replace `$ApplicationId` with a unique character sequence (e.g., your name abbreviation) and `$Password` with a password for protecting your notes. Please note: your password will be transmitted unencrypted over HTTP, so you should use a throwaway password that you are not using anywhere else:

```
$ aws cloudformation create-stack --stack-name notea \
➥ --template-url https:/ /s3.amazonaws.com/\
➥ awsinaction-code3/chapter18/notea.yaml --parameters \
➥ "ParameterKey=ApplicationID,ParameterValue=$ApplicationId" \
➥ "ParameterKey=Password,ParameterValue=$Password" \
➥ --capabilities CAPABILITY_IAM
```

It will take about five minutes until your note-taking app is up and running (figure 18.7). Use the following command to wait until the stack was created successfully and fetch the URL to open in your browser:

```
$ aws cloudformation wait stack-create-complete \
➥ --stack-name notea && aws cloudformation describe-stacks \
➥ --stack-name notea --query "Stacks[0].Outputs[0].OutputValue" \
➥ --output text
```

Congratulations! You have launched a modern web application with ECS and Fargate. Happy note-taking!