④ Authorizes the role to delete data from S3

⑤ Read and write access is granted only to Notea's S3 bucket.

⑥ Allows listing all the objects in the bucket

⑦ The S3 bucket used by Notea to store data

Next, you need to create an ECS service that launches tasks and, with them, containers. The most important configuration details shown in the next listing are:

- `DesiredCount`—Defines the number of tasks the service will launch. The `DesiredCount` will be changed by autoscaling later.
- `LoadBalancers`—The service registers and unregisters tasks at the ALB out of the box with this configuration.

Listing 18.6 Creating an ECS service to spin up tasks running the web app

```
Service:
  DependsOn: HttpListener
  Type: 'AWS::ECS::Service'
  Properties:
    Cluster: !Ref 'Cluster'                          ①
    CapacityProviderStrategy:
    - Base: 0
      CapacityProvider: 'FARGATE'                    ②
      Weight: 1
    DeploymentConfiguration:
      MaximumPercent: 200                            ③
      MinimumHealthyPercent: 100                     ④
      DeploymentCircuitBreaker:                      ⑤
        Enable: true
        Rollback: true
    DesiredCount: 2                                  ⑥
    HealthCheckGracePeriodSeconds: 30                ⑦
    LoadBalancers:                                   ⑧
    - ContainerName: 'app'                           ⑨
      ContainerPort: 3000                            ⑩
      TargetGroupArn: !Ref TargetGroup
    NetworkConfiguration:
```