- A `using` directive that references the project namespace (WebApplication1, in our example)
- A `namespace` directive that sets the namespace for all pages affected by the ViewImports (WebApplication1.Pages)
- An `addTagHelper` directive for managing tag helpers

Tag helpers are components that work with tags in markup to automate HTML generation. They are covered in more detail later in the chapter.

The directives in a ViewImports file affect all .cshtml files located in the same folder and its subfolders. There is no limit to the number of ViewImports files a Razor Pages application can support. You can place additional ViewImports files in subfolders to either add to the top-level ViewImports file's directives or override its settings. Certain directives, such as those for managing tag helpers, the `using` directive, and the `inject` directive (used for making services—covered in chapter 7—available to the page), are additive, while the other directives override each other the closer you get to the page. So, for example, the namespace specified in the ViewImports in the Pages folder will be overridden for pages in a subfolder if a different value is assigned to the `namespace` directive in a ViewImports file in that subfolder.

The second highlighted item in listing 3.1 is a code block. *Code blocks* begin with the `@` symbol, followed by an opening curly brace, then a closing curly brace:

```
@{
    ... C# code goes here
}
```

Anything placed within the code block is pure C# code and must follow the rules of C# syntax. You can include multiple code blocks within a Razor page, but you should aim to keep them to the bare minimum, restricting them only to logic for managing presentation. Having too many code blocks in a Razor page is often a sign that you might have application logic within your UI, which you should avoid because it is very difficult to test when it is mixed in the HTML. For example, the