encourage mixing application code with HTML, making it difficult to reuse, isolate, and test.

An appropriate use of a functions block in a Razor page file would include small routines that manage presentation logic and only apply to the page in which they are placed. They are also useful for your current purpose, which is to simplify the learning of Razor syntax without having to switch between files.

3.1.2 Rendering HTML with expressions

The main purpose of Razor is to render dynamic content as HTML. You have already seen how the value of variables or expressions can be rendered to the browser by placing them inline within the HTML where the value is to be output and prefixing them with the @ symbol:

```
<p>It is @partOfDay on @DateTime.Now.ToString("dddd, dd MMMM")</p>
```

Expressions like this example are known as *implicit expressions*. Another type of expression you will often use within a Razor file is an *explicit expression*, where the expression itself is placed within parentheses and prefixed with the @ symbol. You typically use explicit expressions where there is a space in the expression or where the expression includes angle brackets (i.e., < and >), such as in a generic method. If you don't place such an expression within parentheses, the angle brackets will be seen as HTML. Here's an example of an expression that involves the use of the ternary operator. The expression has spaces within it, so it must be included within the Razor file as an explicit expression:

```
<p>It is @(DateTime.Now.Hour > 12 ? "PM" : "AM")</p>
```

This example will render either `"PM"` or `"AM"` to the browser, depending on the time of day that the expression is executed.

3.1.3 Control blocks in Razor