Server-side code is mainly used in Razor files to control presentational output. Consequently, most of the Razor syntax you use will consist of *control blocks*—selection and iteration statements such as `if-else`, `foreach`, and so on in a page that apply processing logic to conditionally render output or loop through collections of items, for example. These control blocks differ from the code blocks you saw earlier in that they are embedded within the HTML content to be rendered rather than being isolated from the markup within braces.

C# selection and iteration statements are supported within Razor by prefixing the keyword that opens the block with the `@` symbol. The following listing demonstrates how this applies to an `if-else` statement.

Listing 3.4 Selection statement support in Razor

```
@if(DateTime.Now.Hour <= 12)
{
    <p>It is morning</p>
}
else if (DateTime.Now.Hour <= 18)
{
    <p>It is afternoon</p>
}
else
{
    <p>It is evening</p>
}
```

The `if-else` statement works in this example by only rendering one of the paragraphs based on the condition being tested—in this case, the time of day when the page is executed. Note that there is no need for `@` symbols prior to the `else` keywords. In fact, it will cause an error if you attempt to do so.

Listing 3.5 illustrates the use of a `switch` statement as an alternative to the `if-else` block in listing 3.4. Once again, the `@` symbol is only required before the opening `switch` keyword.

Listing 3.5 Switch statement example in Razor

```
@switch (DateTime.Now.Hour)
{
```