```
    case int _ when DateTime.Now.Hour <= 12:
        <p>It is morning</p>
        break;
    case int _ when DateTime.Now.Hour <= 18:
        <p>It is afternoon</p>
        break;
    default:
        <p>It is evening</p>
        break;
}
```

You will often find yourself needing to use iteration statements in Razor pages as you iterate collections for rendering. Let's imagine you are creating a vacation package website, and you need to render a list of possible destinations. The code in the following listing demonstrates the use of the `foreach` statement to render the members of an array of city names as an unordered list.

Listing 3.6 `foreach` statement example in Razor

```
@functions{
    public class City
    {
        public string Name { get; set; }
        public string Country { get; set; }
    }
    List<City> cities = new List<City>{
        new City { Name = "London", Country = "UK" },
        new City { Name = "Paris", Country = "France" },
        new City { Name = "Rome", Country = "Italy" } ,
        new City { Name = "Berlin", Country = "Germany" },
        new City { Name = "Washington DC", Country = "USA" }
    };
}

<ul>
    @foreach (var city in cities)
    {
        <li>@city.Name</li>
    }
</ul>
```

3.1.4 Rendering literal strings

All of the examples so far show Razor transitioning between HTML and C# code. Anything after an @ symbol is considered C# code, until an HTML tag is encountered. Sometimes you might need to render literal strings instead of HTML.